CMAX-D-CPUSEV53



Low PIM Directional In-building Antenna, 698–960 MHz, 1710–2700 MHz

OBSOLETE

This product was discontinued on: July 30, 2022

Replaced By:

CMAX-D-43-V53 Low PIM Directional In-building Antenna, 698-960 MHz, 1710-2700 MHz, 4.3-10

Product Classification

Product Type In-building antenna

General Specifications

Application Indoor

Antenna Type Directional

Antenna Array Characteristic SISO

Polarization Vertical

Color White (RAL 9016)

Mounting 4-hole wall mounting plate and hardware (included)

Number of Ports

Pigtail Cable 670-141SXE, plenum rated

Radome Material ABS

RF Connector Interface N Female

Dimensions

Pigtail Length

 Width
 180 mm | 7.087 in

 Depth
 62 mm | 2.441 in


 Length
 262 mm | 10.315 in

COMMSCOPE®

420 mm | 16.535 in

CMAX-D-CPUSEV53

Outline Drawing



Electrical Specifications

Impedance 50 ohm

Operating Frequency Band 1710 - 2700 MHz | 698 - 960 MHz

Electrical Note Values typical, unless otherwise stated

Electrical Specifications

Frequency Band, MHz	698-800	800-960	1695-1880	1850-1990	1920-2180	2200-2700	2300-2360
Gain, dBi	5.5	6.2	7.3	7.3	7.4	7.6	7.9
Beamwidth, Horizontal, degrees	98	90	73	76	76	76	73
Beamwidth, Vertical, degrees	76	60	60	60	60	57	58
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-153	-153	-153	-153	-153	-153	-153
Input Power per Port, maximum, watts	50	50	50	50	50	50	50

Environmental Specifications

Operating Temperature $-40 \, ^{\circ}\text{C} \text{ to } +60 \, ^{\circ}\text{C} \, (-40 \, ^{\circ}\text{F to } +140 \, ^{\circ}\text{F})$

Relative Humidity Up to 100%

Packaging and Weights

Width, packed 185 mm | 7.283 in

COMMSCOPE®

CMAX-D-CPUSEV53

Depth, packed 85 mm | 3.346 in

Length, packed 320 mm | 12.598 in

Packaging quantity 1

Weight, gross $1 \text{ kg } \mid 2.205 \text{ lb}$ Weight, net $0.9 \text{ kg } \mid 1.984 \text{ lb}$

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



