## L8B0-D8-A00D00-01 | CMC8L



CMC8L Equipment 300W HVAC Empty Micro Cell Site Cabinet

The cabinet is designed to house rack mounted equipment. This includes DC power systems, Fiber storage/splice trays, cell site routers, batteries, and other rack mounted equipment. This cabinet provides mechanical and environmental protection for the equipment inside.

- Excellent Thermal Performance compatible with a DAC or HVAC
- Provides mounting space for power distribution, network servers, batteries, or other equipment.
- Front door compatible with Pad Lock.
- Provides flexible access for the cable entrances.
- Optional heater for cold environments.
- Provides 8RU of 19" or 23" Rack Space for Equipment
- Common parts available across the same platform.

## Product Classification

Product Type Outdoor cabinet

Product Series CMC

## General Specifications

Access Front door | Removable panel

Alarm Type Door alarm | HVAC alarms (including high temperature, failure) | S2 module, 20P or

standard and user defined alarms

**Batteries** Not included

Batteries Supported 3

Capacity 500W Heater

**Color** Gray

**Cooling** Direct air cooling

**Door Security**Quarter turn lock, puck lock system for rear door | Swing handle, puck lock system for front

door

Mounting H-frame | Pad | Pole | Universal wall mount

Noise Emission, maximum 65 dBA

Page 1 of 2



## L8B0-D8-A00D00-01 | CMC8L

Rack Type EIA 19 in | EIA 23 in

Rack Units 8

**Dimensions** 

 Height
 558.8 mm | 22 in

 Width
 711.2 mm | 28 in

 Depth
 711.2 mm | 28 in

Electrical Specifications

**Battery String Current, maximum** 100 A-h @ -48 Vdc

**Battery Strings, quantity** 1 @ -48 Vdc

Cooling Capacity 600 W

Material Specifications

**Finish** Powder coated | UV resistant

Material Type Aluminum

**Environmental Specifications** 

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +46 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +115 \,^{\circ}\text{F})$ 

**Storage Temperature**  $-40 \, ^{\circ}\text{C} \text{ to } +70 \, ^{\circ}\text{C} \, (-40 \, ^{\circ}\text{F to } +158 \, ^{\circ}\text{F})$ 

**Environmental Space**UV resistant for outdoor

**Qualification Standards** IP55 | Telcordia GR-487

Thermal Compliance GR-487

Packaging and Weights

**Weight, net** 40.823 kg | 90 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

