


# SFG23HDXL-13-4-126

---



G23HDXL PIM OPTIMIZED SPACING High Capacity Sector Frame . 2 7 /8in OD x 13ft face with (4) 2-7/8in OD x 126in Antenna pipes

## Product Classification

<b>Product Type</b>	High capacity Tower sector frame
<b>Product Brand</b>	PIM-guard
<b>Product Series</b>	G2

## General Specifications

<b>Mounting</b>	Angle 60°, 203.2 mm (8 in)   Straight or tapered legs up to 203.2 mm (8 in) OD
<b>Patent Number</b>	For patents see: <a href="http://www.cs-pat.com">www.cs-pat.com</a>
<b>Pipe, quantity</b>	4
<b>Sectors, quantity</b>	1
<b>Tower Taper</b>	Non-tapered   Tapered

## Dimensions

<b>Height</b>	3,200.4 mm   126 in
<b>Face Width</b>	3.962 m   13 ft
<b>Platform Width</b>	3,962.4 mm   156 in
<b>Face Support Pipe Diameter</b>	73.025 mm   2.875 in
<b>Mounting Diameter, maximum</b>	203.2 mm   8 in
<b>Mounting Diameter, minimum</b>	38.1 mm   1.5 in
<b>Pipe Outer Diameter</b>	73.025 mm   2.875 in

## Material Specifications

<b>Material Type</b>	Hot dip galvanized steel
----------------------	--------------------------

## Mechanical Specifications

<b>Wind Rating</b>	For Specifications, please contact your local ANDREW representative
<b>Wind Rating Test Method</b>	TIA/EIA-222-G

# SFG23HDXL-13-4-126

---

## Packaging and Weights

<b>Included</b>	Frame   Plain end pipes (4)   Stiff arms (2)   Tower attachment
<b>Packaging quantity</b>	1
<b>Weight, net</b>	471.677 kg   1,039.87 lb

## \* Footnotes

<b>Wind Rating</b>	BWS—Base Wind Speed; FBC—Florida Building Code
--------------------	--