760117390 | 360-PM-GS5-DM-12P



SYSTIMAX 360™ GigaSPEED X10D® 360 PATCHMAX® GS5 Distribution Module

OBSOLETE

This product was discontinued on: July 1, 2011

Replaced By:

760128215 360-PM-GS6-DM12

SYSTIMAX 360[™] GigaSPEED X10D® PATCHMAX® GS6 Distribution Module Kit, 12 port

Product Classification

| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
|------------------------|--|
| Portfolio | SYSTIMAX® |
| Product Type | Module |
| Product Brand | GigaSPEED X10D® SYSTIMAX 360™ |
| General Specifications | |
| ANSI/TIA Category | 6A |
| Cable Type | Unshielded |
| Color | Cool gray |
| Conductor Type | Solid Stranded |
| Intelligence Type | iPatch® ready |
| Modules, quantity | 1 |
| Termination Type | IDC |
| Total Ports, quantity | 12 |
| Wiring | T568A T568B |
| Dimensions | |
| Height | 73.66 mm 2.9 in |
| Width | 109.22 mm 4.3 in |
| Depth | 38.1 mm 1.5 in |

Page 1 of 3

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 4, 2020



360-PM-GS5-DM-12P 760117390

| Compatible Diameter Over Dielectric, maximum | 1.168 mm 0.046 in |
|---|---|
| Compatible Diameter Over Dielectric, minimum | 0.762 mm 0.03 in |
| Compatible Conductor Gauge, solid | 22 AWG 24 AWG |
| Compatible Conductor Gauge, stranded | 22 AWG 24 AWG |
| Electrical Specifications | |
| Current Rating at Temperature | 1.5 A @ 20 °C 1.5 A @ 68 °F |
| Dielectric Withstand Voltage, RMS, conductive surface | 1,500 Vac @ 60 Hz |
| Dielectric Withstand Voltage, RMS, contact-to-contact | 1,000 Vac @ 60 Hz |
| Insulation Resistance, minimum | 500 MOhm |
| Material Specifications | |
| Contact Plating Material | Precious metals |
| Material Type | High-impact, flame retardant, thermoplastic |
| Termination Contact Plating | Nickel |
| Mechanical Specifications | |
| Plug Insertion Life, minimum | 750 times |
| Plug Insertion Life, test plug | IEC 60603-7 compliant plug |
| Plug Retention Force, minimum | 133.447 N 30 lbf |
| | |
| Environmental Specifications | |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
| Relative Humidity | Up to 95%, non-condensing |
| Flammability Rating | UL 94 V-0 |
| Safety Standard | UL cUL |
| Packaging and Weights | |

Packaging quantity

1

Regulatory Compliance/Certifications

Classification

ISO 9001:2015

Agency

Designed, manufactured and/or distributed under this quality management system

Page 2 of 3

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 4, 2020



760117390 | 360-PM-GS5-DM-12P



Page 3 of 3

©2020 CommScope, Inc. All rights reserved. All trademarks identified by ® or [™] are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: November 4, 2020

