

Termination Manager Kit for Unshielded Distribution Module Panel

Product Classification

Regional Availability Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®

Product Type Termination manager

General Specifications

ANSI/TIA Category 5 | 5e | 6 | 6A

Color White

Dimensions

 Height
 12.7 mm | 0.5 in

 Width
 14.732 mm | 0.58 in

 Depth
 9.144 mm | 0.36 in

Material Specifications

Material Type High-impact, flame retardant, thermoplastic

Environmental Specifications

Operating Temperature $-10 \,^{\circ}\text{C}$ to $+60 \,^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +140 $^{\circ}\text{F}$)

Storage Temperature $-40 \,^{\circ}\text{C}$ to $+70 \,^{\circ}\text{C}$ (-40 $^{\circ}\text{F}$ to +158 $^{\circ}\text{F}$)

Flammability Rating UL 94 V-0
Safety Standard UL | cUL

Packaging and Weights

Packaging quantity 24

Regulatory Compliance/Certifications

Agency Classification

COMMSCOPE®

760199760

CHINA-ROHS Below maximum concentration value

Compliant

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant





