

## GigaSPEED X10D® 1100GS5 Angled Category 6A U/UTP 2U Panel Kit

### **OBSOLETE**

#### Replaced By:

760105668  
1100A-GS6-2U

GigaSPEED X10D® 1100GS6 Angled Category 6A U/UTP 2U Panel Kit

## Product Classification

### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

### Portfolio

SYSTIMAX®

### Product Type

RJ45 patch panel

### Product Brand

GigaSPEED X10D®

## General Specifications

### Cable Type

Unshielded

### Color

Black

### Conductor Type

Solid | Stranded

### Intelligence Type

Passive

### Panel Style

Angled

### Rack Type

EIA 19 in

### Rack Units

2

## Dimensions

### Height

88.9 mm | 3.5 in

### Width

482.6 mm | 19 in

### Depth

40.64 mm | 1.6 in

### Compatible Conductor Gauge, solid

22 AWG | 24 AWG

### Compatible Conductor Gauge, stranded

22 AWG | 24 AWG

## Electrical Specifications

### Current Rating at Temperature

1.5 A @ 20 °C | 1.5 A @ 68 °F

### Dielectric Withstand Voltage, RMS, conductive surface

1,500 Vac @ 60 Hz

# 760092833 | 1100A-GS5-2U

---

**Dielectric Withstand Voltage, RMS, contact-to-contact** 1,000 Vac @ 60 Hz

**Insulation Resistance, minimum** 500 MOhm

## Material Specifications

**Material Type** Powder-coated steel

## Environmental Specifications

**Operating Temperature** -10 °C to +60 °C (+14 °F to +140 °F)

**Storage Temperature** -40 °C to +70 °C (-40 °F to +158 °F)

**Relative Humidity** Up to 95%, non-condensing

**Flammability Rating** UL 94 V-0

**Safety Standard** UL | cUL

## Regulatory Compliance/Certifications

### Agency

ISO 9001:2015

### Classification

Designed, manufactured and/or distributed under this quality management system

