760202580 | 360-iP-MFTPA-E-HD6B-2U-48



SYSTIMAX 360™ iPatch® Evolve High Density F/UTP Angled Modular Panel, 48 port

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin

America | North America

Portfolio SYSTIMAX®

Product Type RJ45 patch panel

Product Brand SYSTIMAX 360™ | iPatch®

General Specifications

ANSI/TIA Category 6 | 6A | 6A | Cable Type Shielded | Color | Cool gray

Intelligence Type iPatch® enabled

Panel Style Angled

Rack Units 2

Total Ports, quantity 48

Wiring T568A | T568B

Dimensions

Height 88.9 mm | 3.5 in

Width 482.6 mm | 19 in

Depth 266.7 mm | 10.5 in

Compatible Diameter Over Dielectric, maximum 1.168 mm | 0.046 in

Compatible Diameter Over Dielectric, minimum 0.762 mm | 0.03 in

Electrical Specifications

Current Rating at Temperature 1.5 A @ 20 °C | 1.5 A @ 68 °F

Dielectric Withstand Voltage, RMS, conductive surface1,500 Vac @ 60 HzDielectric Withstand Voltage, RMS, contact-to-contact1,000 Vac @ 60 Hz

Page 1 of 2



760202580 | 360-iP-MFTPA-E-HD6B-2U-48

Insulation Resistance, minimum

500 MOhm

Material Specifications

Material Type

Acrylonitrile butadiene styrene (ABS) | Polycarbonate

Environmental Specifications

Operating Temperature -5 °C to +50 °C (+23 °F to +122 °F)

Storage Temperature $-40 \,^{\circ}\text{C} \text{ to } +70 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +158 \,^{\circ}\text{F})$

Relative Humidity Up to 95%, non-condensing

Flammability Rating UL 94 V-0

Safety Standard ACMA | CE | ETL | UL

Packaging and Weights

Included Cable management bar | Four #12-24 dog point mounting

screws | Instruction sheet | Modular jacks

(48) | Panel | Two #12 washers | Two #12-24 screws

Packaging quantity

Weight, net 2.722 kg | 6 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted





