## CTAJB | IP6A-06BFTP-01S-PG2H

#### **Base Product**



InstaPATCH® Cu GigaSPEED X10D® F/FTP LSZH Class B2ca Preterminated Copper Cable, single row standard density outlet to dual row high density RJ45 plug, 6 links

#### **Product Classification**

Regional Availability EMEA

Portfolio CommScope®

Product Type Copper trunk cable assembly

Product Brand GigaSPEED X10D® | InstaPATCH® Cu

Ordering Note Available cable jacket color: white

General Specifications

ANSI/TIA Category 6A

Cable Type F/FTP (shielded) | S/FTP (shielded)

Conductor Type Solid

Interface, Connector A Information outlet

Interface Feature, connector A Single row | Standard density

Interface, Connector B RJ45 plug

Interface Feature, connector B Dual row | High density

Link Count 6

Wiring T568B

**Dimensions** 

Cable Assembly Length Range (m) 5 – 90

Cable Assembly Length Range (ft) 17 – 295


**Electrical Specifications** 

dc Resistance, maximum0.3 ohmSafety Voltage Rating300 V

Ordering Tree



## CTAJB | IP6A-06BFTP-01S-PG2H



### **Environmental Specifications**

**EN50575 CPR Cable EuroClass Acidity Rating** 

Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

EN50575 CPR Cable EuroClass Fire PerformanceB2caEN50575 CPR Cable EuroClass Smoke Ratings1EN50575 CPR Cable EuroClass Droplets Ratingd0

**Environmental Space** Low Smoke Zero Halogen (LSZH)

Flammability Rating UL 94 V-0

#### Regulatory Compliance/Certifications

Agency	Classification
CENELEC	EN 50575 compliant, Declaration of Performance (DoP) available
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

a1



CENELEC -



# CTAJB | IP6A-06BFTP-01S-PG2H

760237952 3296A-B WH 4/23 R1640  3296A-B Category 6A F/FTP Cable, low smoke zero halogen, white jacket, 4 pair count, 1640 ft (500 m) length, reel