DB589-Y

1-port omni antenna, 890-960 MHz, 360° HPBW, fixed electrical tilt, fits on 38-60 mm (1-1/2 to 2 3/8 in) OD pipe

- Light weight, low profile omnidirectional antenna ideal for low to moderate gain applications
- Integral dual purpose mount allows top or side mounting

General Specifications

Antenna Type Omni

Band Single band
Color Horizon blue

Grounding Type RF connector inner conductor and body grounded to reflector and mounting bracket

Performance Note Outdoor usage

Radome Material Fiberglass, UV resistant

Radiator MaterialBrassRF Connector InterfaceN FemaleRF Connector LocationBottom

RF Connector Quantity, low band 1
RF Connector Quantity, total 1

Dimensions

Length 2476 mm | 97.48 in

Net Weight, without mounting kit 5.2 kg | 11.464 lb

Outer Diameter 38.1 mm | 1.5 in

Electrical Specifications

Impedance 50 ohm

Operating Frequency Band 890 – 960 MHz

Polarization Vertical

Electrical Specifications

Frequency Band, MHz 890-960
Gain, dBi 11.1
Beamwidth, Horizontal, 360

COMMSCOPE®

DB589-Y

degrees

Beam Wilt, Vertical, degrees 9 **Beam Tilt, degrees** 0

VSWR | Return loss, dB 1.5 | 14.0 PIM, 5th Order, 2 x 20 W, dBc -153 Input Power per Port, 400

maximum, watts

Mechanical Specifications

Wind Loading @ Velocity, maximum 176.1 N @ 100 mph (39.6 lbf @ 100 mph)

Wind Speed, maximum 201 km/h (125 mph)

Packaging and Weights

Included V-bolts

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance

