



LSA-PLUS® Series 2

Disconnection Modules

A technically and commercially superior quick connection system for all state-of-the-art networks. Contacts that ensure the highest degree of reliability even under the most adverse environmental and climatic conditions. A completely reliable, gas-tight connection between the contact and conductor. That's LSA-PLUS® technology.

The LSA-PLUS System family consists of a comprehensive and diverse range of high density, standard and special modules, mounting hardware, test and patch cords, accessories and protection devices.

Voice, high-speed data transmission via ISDN, ADSL, VDSL, cable TV, Internet access, mobile networks – working in conjunction with CommScope you will be able to confidently face the issues created by vast amounts of network traffic. In addition, CommScope quality ensures total end-customer satisfaction. CommScope copper connectivity solutions are designed to deliver fast, safe and reliable transmission.

Features and Benefits

- Eight- and ten-pair modules with disconnection points for opening the line, testing in both directions or insertion of graded protection elements
- Based on genuine LSA-PLUS connection technology
- LSA-PLUS modules mount on back mount frames
- LSA PROFIL® modules mount on profile rods (8-pair modules: 75 or 95mm spacing between rods; 10-pair modules: 95mm spacing between rods) or on back mount frames
- Suitable for use in all xDSL and ADSL2+ circuits
- Robust long-term environmental stability allows both indoor and outdoor installation
- Supports all LSA-PLUS Series 2 accessories
 - Overvoltage protection
 - Labels
 - Test and connection cords

Specifications

Electrical Values

Insulation resistance:	>50 GΩ @ 500 V
Contact resistance:	1 mΩ

Safety Classification (EN 60950)

Transient voltage:	2.5k V
Operation voltage for basic insulation:	210VDC TNV
Pollution severity:	II
Current-carrying capacity:	2 A
Impulse current:	5 kA (8/2μs)

Conductor Diameter/Outer Diameter of Connectable Wires

Single solid wire per contact:	0.35mm/0.68mm to 0.9mm/1.5mm AWG 26 to AWG 20
Stranded wires (7 tin-coated copper strands):	0.12mm to 0.32mm/up to 2.1 mm (depending on insulation type)
Overall diameter of connectable wires: (solid insulation)	0.68mm to 1.6mm

Properties

Connection frequency:	200 times
Plug-in cycles:	250

Temperature

Storage (EN 60721-3-1):	1K5 (-40° C to +90° C)/1Z1/1B1/1C1/1S1/1M2
Transport (EN 60721-3-2):	2K2 (-40° C to +90° C)/2B1/2C1/2S1/2M2
Operation (EN 60721-3-3):	3K5 (-5° C to +60° C)/3Z1/3B1/3C1/3S1/3M2
Relative humidity:	95%; no water condensation, no ice

Materials

Plastics:	PBT; resistant against aggressive chemicals (PVC-softener)
Plastics flammability class:	UL94V-0
Halogen free according to:	RoHS, European Directive 2002/96/EG
Contact:	Special brass, silver-plated



www.commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

LSA-PLUS, LSA PROFIL and all trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc.

This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-312078.1-EU (01/16)