

**FACT-CTU-M-IFC**


**NOTE:**

- the cable termination unit is designed to accommodate up to 4x IFC-cable with a maximum cable diameter of 7mm
- the cable needs to be flexible enough and allow a minimum bend radius less than 75mm
- the kit contains all parts to install 4 pieces of IFC cable on 1 FACT-element

<b>CONTENT</b>	<b>1</b>	<b>General</b> 1.1 Kit content 1.2 Tools required 1.3 Example drawing
	<b>2</b>	<b>Cable preparation</b> 2.1 General cable preparation
	<b>3</b>	<b>Routing and termination on FACT - splice element</b>
	<b>4</b>	<b>Routing and termination on FACT - splice/patch element</b>

**1 General**

1.1 Kit content




- 1x Cable termination unit medium
- 1x Cover cable termination unit medium
- 2x Wrap-around flex-tube 430mm
- 4x Foam
- 8x Tie-wrap black
- 1x Allen key

1.2 Tool required


Standard installation tooling for fiber optic cable

### 1.3 Example drawing



## 2 Cable preparation


### 2.1 General cable preparation



- 2.1.1 - mark the stripping point on the cable jacket  
- make sure you have at least 2 meters of cable left



- 2.1.2 Cut the cable jacket at the marked point and approx. 150mm from the cable end to get access to the rip-cord




- 2.1.3 Use the rip-cord to strip off the cable jacket




- 2.1.4 - Separate the amide yarn from the 900µm carefully  
- Turn the amide yarn  
- Apply a foam  
- Cut off the unnecessary amide yarn






2.1.5 Fix all 4 cables with 2 tie-wraps and cut them




2.1.6 Install the cover


### 3 Routing and termination on FACT – splice element



3.1 Install the tie-wraps like shown in the picture




3.2 Route IFC-1 over the top trumpets, IFC-2 and IFC-3 in between and IFC-4 under the lower trumpets and feed 24 fibers each through both flex-tubes




3.3 Fix the flex-tube with tie-wrap like shown in the picture



3.4 Install the tie-wrap like shown in the picture




3.5 Open the orange covers and guide the flex-tube into the splice drawer




3.6 Fix the flex-tube with tie-wrap on splice drawer Repeat this steps for the second IFC-cable as well






3.7 Route the fiber throughout the groove plate to the dedicated splice trays




3.8 Route the 900 $\mu$ m fiber to the splice tray and mark the stripping point to 250 $\mu$ m (stripping zone marked on tray)




3.9 Strip the 900 $\mu$ m to 250 $\mu$ m with a proper tool




3.10 Check the proper routing of the fiber into the splice tray




3.11 Attention to correct fiber storage - A properly stored fiber don't touch the bend radius limiter on inner or outer side and can move freely



## 4 Routing and termination on FACT – splice/patch element




4.1 Install the tie-wrap like shown in the picture



4.2 In case the IFC-cable is already connectorized:  
Split the flex-tube into two half, it's a wrap-around  
flex-tube



4.3 If you bend the flex-tube the slot becomes slightly bigger,  
so that the 900µm fiber can be installed easier  
Close the flex-tube with the second half carefully



4.4 Fix the flex-tube on the splice-patch tray with a tie-wrap





---

**CommScope Connectivity Belgium bvba**

Diestsesteenweg 692  
B-3010 Kessel-Lo, Belgium  
Tel.: 32-16-351 011  
Fax: 32-16-351 697  
commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc.  
This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to  
CommScope products or services.

TC 1338/3/IP/1 07/16