

VD-S3-CPUSE-H-N



ValuDAS™, Three-way Reactive Power Splitter, 698–2700 MHz, DC Pass all ports (Additional mounting bracket PN:42396A-17 sold separately)

OBSOLETE

This product was discontinued on: June 29, 2023

Replaced By:

VD-S3-CPUSEW-H-43B ValuDAS™, Multiband Three-way Reactive High Power Splitter, 578–3800 MHz, 4.3-10

Product Classification

Regional Availability	Asia EMEA Latin America
Product Type	Power splitter
Product Brand	ValuDAS®
Ordering Note	Available in Central and Latin America, Europe, Middle East, Africa, and Asia Pacific

General Specifications

Device Type	Splitter
Application	Indoor
Color	Black
Inner Contact Plating	Silver
Interface	N Female
Outer Contact Plating	Trimetal

Dimensions

Height	23 mm 0.906 in
Width	59 mm 2.323 in
Length	279 mm 10.984 in

Electrical Specifications

3rd Order IMD	-155 dBc
3rd Order IMD Test Method	Two +43 dBm carriers

VD-S3-CPUSE-H-N

Return Loss, minimum	20.8 dB
Average Power, maximum	300 W
Dissipative Loss at Frequency Band	0.3 dB @ 698–2700 MHz
Impedance	50 ohm
Operating Frequency Band	698 – 2700 MHz
Peak Power, maximum	3 kW
Power Rating, Splitting	300 W
Reflected Power, maximum	300 W
Split Loss	4.8 dB
VSWR	1.2

Environmental Specifications

Operating Temperature	-35 °C to +85 °C (-31 °F to +185 °F)
Relative Humidity	Up to 100%
Ingress Protection Test Method	IEC 60529:2001, IP65

Packaging and Weights

Height, packed	42 mm 1.654 in
Width, packed	77 mm 3.031 in
Length, packed	315 mm 12.402 in
Volume	1018700 mm ³ 62.165 in ³
Weight, gross	0.43 kg 0.948 lb
Weight, net	0.38 kg 0.838 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

