


NNH4S4-65C-R7



20 Port Sector Antenna & Beamforming , 4x698-896 MHz, 8x1695-2360 MHz, 65° HPBW and 8x3400-4000 MHz Beamformer, 7XRET

- Multi-band FDD antenna featuring C-Band 8T8R functionality
- Feature the same dimensions as existing 8 and 12-port FDD capable antennas
- New endcap designs provide improved wind loading performance
- The C-band RET is factory set to AISG2. All other RET are assigned to AISG1
- The antenna is supplied with mounting kits that provide 0 degree of mechanical downtilt; optional downtilt mounting kits are available

General Specifications

Antenna Type	Sector- and beamforming
Band	Multiband
Calibration Connector Interface	4.3-10 Female
Calibration Connector Quantity	1
Color	Light Gray (RAL 7035)
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	Fiberglass, UV resistant
Radiator Material	Low loss circuit board
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	8
RF Connector Quantity, mid band	8
RF Connector Quantity, low band	4
RF Connector Quantity, total	20

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	2 female 2 male
Input Voltage	10-30 Vdc



NNH4S4-65C-R7

Internal RET	High band (1) Low band (2) Mid band (4)
Power Consumption, active state, maximum	8 W
Power Consumption, idle state, maximum	1 W
Protocol	3GPP/AISG 2.0 (Multi-RET)

Dimensions

Width	498 mm 19.606 in
Depth	197 mm 7.756 in
Length	2438 mm 95.984 in
Net Weight, antenna only	52 kg 114.64 lb
TDD Column Spacing	41 mm 1.614 in


Array Layout



Array ID	Frequency (MHz)	RF Connector	RET (IMRET)	AISG No.	AISG RET UID
R1	698-896	1 - 2	1	AISG1	CPxxxxxxxxxxxxMM.1
R2	698-896	3 - 4	2	AISG1	CPxxxxxxxxxxxxMM.2
Y1	1695-2360	5 - 6	3	AISG1	CPxxxxxxxxxxxxMM.3
Y2	1695-2360	7 - 8	4	AISG1	CPxxxxxxxxxxxxMM.4
Y3	1695-2360	9 - 10	5	AISG1	CPxxxxxxxxxxxxMM.5
Y4	1695-2360	11 - 12	6	AISG1	CPxxxxxxxxxxxxMM.6
P1	3400-4200	13 - 20	7	AISG2	CPxxxxxxxxxxxxMM.1

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration



NNH4S4-65C-R7

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1695 – 2360 MHz 3400 – 4000 MHz 698 – 896 MHz
Polarization	±45°
Total Input Power, maximum	1,500 W @ 50 °C

Electrical Specifications

	R1-R2	R1-R2	Y1-Y4	Y1-Y4	Y1-Y4	Y1-Y4	P1	P1
Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2180	2300–2360	3400–3700	3700–4000
RF Port	1-4	1-4	5-12	5-12	5-12	5-12	13-20	13-20
Gain, dBi	15.6	16.1	17	17.5	18.1	18.6	16	17.2
Beamwidth, Horizontal, degrees	71	64	71	69	63	56	96	79
Beamwidth, Vertical, degrees	9.6	8.2	5.9	5.4	5.1	4.6	6.1	5.7
Beam Tilt, degrees	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10
USLS (First Lobe), dB	15	16	16	16	16	16	15	16
Front-to-Back Ratio at 180°, dB	32	31	34	35	35	35	31	30
Coupling level, Amp, Antenna port to Cal port, dB							26	26
Coupling level, max Amp Δ, Antenna port to Cal port, dB							±2	±2
Coupler, max Amp Δ, Antenna port to Cal port, dB							0.6	0.6
Coupler, max Phase Δ, Antenna port to Cal port, degrees							5	5
Isolation, Cross Polarization, dB	25	25	25	25	25	25	25	25
Isolation, Inter-band, dB	25	25	25	25	25	25	25	25
Isolation, Co-polarization, dB							19	19
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150	-145	-145
Input Power per Port at 50°C, maximum, watts	300	300	250	250	250	200	75	75

Electrical Specifications, BASTA

NNH4S4-65C-R7

Frequency Band, MHz	698–806	806–896	1695–1880	1850–1990	1920–2180	2300–2360	3400–3700	3700–4000
Gain by all Beam Tilts, average, dBi	15.2	15.8	16.5	17.2	17.7	18.3	15.6	16.4
Gain by all Beam Tilts Tolerance, dB	±1.6	±1.6	±1.6	±1.6	±1.6	±1.6	±1.6	±1.6
USLS, beampeak to 20° above beampeak, dB	15	16	15	15	16	16	13	12
Front-to-Back Total Power at 180° ± 30°, dB	23	23	27	27	28	27	24	24
CPR at Boresight, dB	21	23	20	22	23	23	15	14
CPR at Sector, dB	13	10	12	12	8	8	6	7

Electrical Specifications, Broadcast 65°

Frequency Band, MHz	3400–3700	3700–4000
Gain, dBi	18	19
Beamwidth, Horizontal, degrees	65	65
Beamwidth, Vertical, degrees	6.1	5.7
Beamwidth, Vertical Tolerance, degrees	±0.3	±0.3
Front-to-Back Total Power at 180° ± 30°, dB	27	27
USLS (First Lobe), dB	17	19

Electrical Specifications, Envelope Pattern

Frequency Band, MHz	3400–3700	3700–4000
Gain, dBi	20.9	21.7

Electrical Specifications, Service Beam

Frequency Band, MHz	3400–3700	3700–4000
Steered 0° Gain, dBi	20.9	21.6
Steered 0° Beamwidth, Horizontal, degrees	25	24
Steered 0° Front-to-Back Total Power at 180° ± 30°, dB	30	30
Steered 30° Gain, dBi	19.3	20.1
Steered 30° Beamwidth, Horizontal, degrees	34	30
Steered 30° Front-to-Back Total Power at 180° ± 30°, dB	29	29

NNH4S4-65C-R7

Electrical Specifications, Soft Split

Frequency Band, MHz	3400–3700	3700–4000
Gain, dBi	19.4	20.1
Beamwidth, Horizontal, degrees	36	30
Front-to-Back Total Power at 180° ± 30°, dB	30	30
Horizontal Sidelobe, dB	17	16
USLS (First Lobe), dB	19	20

Mechanical Specifications

Effective Projective Area (EPA), frontal	0.81 m ² 8.719 ft ²
Effective Projective Area (EPA), lateral	0.25 m ² 2.691 ft ²
Wind Loading @ Velocity, frontal	865.0 N @ 150 km/h (194.5 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	268.0 N @ 150 km/h (60.2 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,037.0 N @ 150 km/h (233.1 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	595.0 N @ 150 km/h (133.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	565 mm 22.244 in
Depth, packed	309 mm 12.165 in
Length, packed	2625 mm 103.347 in
Weight, gross	67.4 kg 148.591 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant



Included Products

NNH4S4-65C-R7

BSAMNT-3F

- Mounting bracket for cylindrical pipe installations (60-115mm pipe diameter) for fix mechanical tilt applications.

* Footnotes

Performance Note

Severe environmental conditions may degrade optimum performance