


SFG21HD-10-B



G21HD High Capacity Sector Frame, 10.5 ft x 2.88 in OD face pipes, Base Kit Only. No antenna pipes.

Product Classification

| | |
|-----------------------|----------------------------------|
| Product Type | High capacity Tower sector frame |
| Product Series | G2 |

General Specifications

| | |
|--------------------------|--|
| Application | 4G LTE antenna/radio mount |
| Mounting | Angle 60°, 203.2 mm (8 in) Straight or tapered legs up to 203.2 mm (8 in) OD |
| Patent Number | Patent pending |
| Pipe, quantity | 0 |
| Sectors, quantity | 1 |
| Tower Taper | Non-tapered Tapered |

Dimensions

| | |
|-----------------------------------|----------------------|
| Face Width | 3.2 m 10.5 ft |
| Width | 3,200.4 mm 126 in |
| Face Support Pipe Diameter | 73.025 mm 2.875 in |
| Mounting Diameter, maximum | 218.44 mm 8.6 in |
| Mounting Diameter, minimum | 38.1 mm 1.5 in |
| Stand-off Distance | 889 mm 35 in |

Material Specifications

| | |
|----------------------|--------------------------|
| Material Type | Hot dip galvanized steel |
|----------------------|--------------------------|

Mechanical Specifications

| | |
|--------------------------------|--|
| Wind Rating | For Specifications, please contact steelproducts@commscope.com or call 800-255-1479 |
| Wind Rating Test Method | TIA/EIA-222-G |

Packaging and Weights

SFG21HD-10-B

Included Frame | Pipe mounts | Stiff arm | Tower attachment

Packaging quantity 1

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code